

## **Philosophy of Logic – Reexamining the Formalized Notion of Truth**

Because formal systems of symbolic logic inherently express and represent the deductive inference model formal proofs to theorem consequences can be understood to represent sound deductive inference to deductive conclusions without any need for other representations.

To put this in laymen's terms all of the truth that can be expressed using words or math symbols is anchored in sentences that are defined to be true: "A cat is an animal".

Other true sentences are derived from this basic set:

- (1) A cat is an animal.
- (2) Animals breath.
- (3) Therefore cats breath.

The basic truths of English would be called axioms in math.

The derived truths of English would be called theorems in math.

It turns out that all conceptual truth works this same way.

I am approaching these things from the frame of reference of the Tarski Undefinability Proof. I created Minimal Type Theory as a universal Tarski metalanguage eliminating the need to switch back and forth and mix and match between a meta-language and a separate object language.

### **Instead of Tarski's unnecessarily convoluted analysis:**

Since, moreover, the metatheory can be interpreted in the theory enriched by variables of higher order (cf. p. 184) and since in this interpretation the sentence  $x$ , which contains no specific term of the metatheory, is its own correlate, the proof of the sentence  $x$  given in the metatheory can automatically be carried over into the theory itself: the sentence  $x$  which is undecidable in the original theory becomes a decidable sentence in the enriched theory.

### **We refer to this Tarski definition:**

the metalanguage to be so constructed that the language we are studying forms a fragment of it ; every expression of the language is at the same time an expression of the metalanguage,

to simply do all of the analysis directly within a single language capable of directly expressing unlimited levels of logic. MTT is its own meta-language.

The other great thing about MTT is that it has its own provability operator thus no need to go through the cumbersome process of artificially contriving a provability predicate in a language that is woefully inadequate for this task. Expressions in a language with its own provability operator can be directly examined within the deductive inference model.

First we lay the foundation of expressing semantic truth directly within a formal system. All of semantic truth has its ultimate ground of being in expressions of language that have been defined to be true.

[https://en.wikipedia.org/wiki/Theory\\_\(mathematical\\_logic\)](https://en.wikipedia.org/wiki/Theory_(mathematical_logic))

The construction of a theory begins by specifying a definite non-empty conceptual class E the elements of which are called statements. These initial statements are often called the primitive elements or elementary statements of the theory, to distinguish them from other statements which may be derived from them.

A theory T is a conceptual class consisting of certain of these elementary statements. The elementary statements which belong to T are called the elementary theorems of T and said to be true. In this way, a theory is a way of designating a subset of E which consists entirely of true statements. (Haskell Curry, Foundations of Mathematical Logic, 2010).

From this basis we can infer that every formal proof of theorems in such a (Haskell Curry) formal system would exactly correspond to deriving the conclusion of sound deductive inference. R. B. Braithwaite explains this in depth below:

KURT GÖDEL

Translated by B. MELTZER

Introduction by R. B. BRAITHWAITE

2 INTRODUCTION

In order to show that in a deductive system every theorem follows from the axioms according to the rules of inference it is necessary to consider the formulae which are used to express the axioms and theorems of the system, and to represent the rules of inference by rules Gödel calls them “mechanical” rules, p. 37) according to which from one or more formulae another formula may be obtained by a manipulation of symbols. Such a representation of a deductive system will consist of a sequence of formulae (a calculus) in which the initial formulae express the axioms of the deductive system and each of the other formulae, which express the theorems, are obtained from the initial formulae by a chain of symbolic manipulations. **The chain of symbolic manipulations in the calculus corresponds to and represents the chain of deductions in the deductive system.**

But this correspondence between calculus and deductive system may be viewed in reverse, and by looking at it the other way round Hilbert originated metamathematics. Here a calculus is constructed, independently of any interpretation.

From the above we can see that the formal proof to theorem consequences expressed in symbolic logic represents and expresses sound deductive inference to deductive conclusions. One way to look at this might be that formal proof to theorem consequences corresponds to and expresses the sound deductive inference model.

Since the conclusions of sound deductive inference are understood to be true we can formulate this universal truth predicate:

**$\forall F \in \text{Formal\_Systems } \forall x \in \text{WFF}(F) (\text{True}(F, x) \leftrightarrow (F \vdash x))$**

MTT is intended to be used as a universal Tarski meta-language including a meta-language to itself. This eliminates messy mixing and matching between his object language and metalanguage. There is no need to force-fit meta-language variables directly into the object language or otherwise move back and forth between two languages. We simply have one language that can express anything.

```

%left IDENTIFIER          // Letter+ (Letter | Digit)* // Letter includes UTF-8
%left SUBSET_OF           // ⊆
%left ELEMENT_OF         // ∈
%left FOR_ALL             // ∀
%left THERE_EXISTS       // ∃
%left IMPLIES            // →
%left PROVES             // ⊢
%left IFF                 // ↔
%left AND                 // ∧
%left OR                  // ∨
%left NOT                 // ~
%left ASSIGN_ALIAS       // := LHS is assigned as an alias name for the RHS (macro substitution)
%%

sentence
: atomic_sentence
| '~' sentence %prec NOT
| '(' sentence ')'
| sentence IMPLIES sentence
| sentence IFF sentence
| sentence AND sentence
| sentence OR sentence
| quantifier IDENTIFIER sentence
| quantifier IDENTIFIER type_of IDENTIFIER sentence // Enhancement to FOL
| sentence PROVES sentence // Enhancement to FOL
| IDENTIFIER ASSIGN_ALIAS sentence // Enhancement to FOL
;

atomic_sentence
: IDENTIFIER '(' term_list ')' // ATOMIC PREDICATE
| IDENTIFIER // SENTENTIAL VARIABLE // Enhancement to FOL
;

term
: IDENTIFIER '(' term_list ')' // FUNCTION
| IDENTIFIER // CONSTANT or VARIABLE
;

term_list
: term_list ',' term
| term
;

type_of
: ELEMENT_OF // Enhancement to FOL
| SUBSET_OF // Enhancement to FOL
;

quantifier
: THERE_EXISTS
| FOR_ALL
;

```