Halting problem proofs refuted on the basis of software engineering?

This is an explanation of a possible new insight into the halting problem provided in the language of software engineering. Technical computer science terms are explained using software engineering terms. No knowledge of the halting problem is required.

It is based on fully operational software executed in the x86utm operating system. The x86utm operating system (based on an excellent open source x86 emulator) was created to study the details of the halting problem proof counter-examples at the much higher level of abstraction of C/x86.

```
typedef void (*ptr)();
int H(ptr p, ptr i); // simulating halt decider

void P(ptr x)
{
   int Halt_Status = H(x, x);
   if (Halt_Status)
       HERE: goto HERE;
   return;
}
int main()
{
   Output("Input_Halts = ", H(P, P));
}
```

When simulating halt decider H(P,P) simulates its input it can see that:

- (1) Function H() is called from P().
- (2) With the same arguments to H().
- (3) With no control flow instructions in P preceding its invocation of H(P,P) that could escape repeated simulations.

This is the same criteria used for infinite recursion detection that has been adapted so that it does not need static local memory to see that the same function has been called with the same arguments twice in sequence with no conditional-branch escape.

Because H knows its own machine address H need not see P call H(P,P) more than once because H already knows that it was called with these same arguments. This eliminates the need for H to have static local memory that communicates between different invocations of itself.

The above shows that the simulated P cannot possibly (reachs it "return" instruction and) terminate normally. H(P,P) simulates its input then P calls H(P,P) to simulate itself again. When H sees that this otherwise infinitely nested simulation would never end it aborts its simulation of P and rejects P as non-halting.

In computability theory, the halting problem is the problem of determining, from a description of an arbitrary computer program and an input, whether the program will finish running, or continue to run forever. Alan Turing proved in 1936 that a general algorithm to solve the halting problem for all possible program-input pairs cannot exist.

For any program H that might determine if programs halt, a "pathological" program P, called with some input, can pass its own source and its input to H and then specifically do the opposite of what H predicts P will do. **No H can exist that handles this case.** https://en.wikipedia.org/wiki/Halting_problem

H and P implement the exact pathological relationship to each other as described above. Because H(P,P) does handle this case the above halting problem undecidable input template has been refuted.

When this halt deciding principle understood to be correct:

A halt decider must compute the mapping from its inputs to an accept or reject state on the basis of the actual behavior that is actually specified by these inputs.

Within the common knowledge that the correct simulation of a program (or TM description) accurately measures the actual behavior of this program:

Then (by logical necessity) this correctly implements the halting deciding principle: Every simulating halt decider that correctly simulates its input until it correctly predicts that this simulated input would never terminate normally, correctly rejects this input as non-halting.

H may or may not be an actual computable function. In any case H should at least apply to the <u>Termination analysis</u>. It really seems that H is a <u>Pure function</u> thus implements a <u>Computable function</u> Thus H is Turing computable.

A halt decider must compute the mapping from its inputs to an accept or reject state on the basis of the actual behavior that is actually specified by these inputs.

It is common knowledge that a correct simulation of a program is a correct measure of the behavior of this program. The concept of a Universal Turing Machine (UTM) is invalidated unless it is accepted that the correct simulation of a machine description is computationally equivalent to the underlying computation.

Example 03 shows the details of the execution trace of H(P,P) proving that this input would never reach its "C:"return" or x86:"ret" instruction.

computation that halts ... the Turing machine will halt whenever it enters a final state. (Linz:1990:234)

Linz, Peter 1990. An Introduction to Formal Languages and Automata. Lexington/Toronto: D. C. Heath and Company. (317-320)

07/25/22 09:01:24 AM

Example 01: H0 correctly determines that Infinite_Loop() never halts

```
void Infinite_Loop()
    HERE: goto HERE;
}
int main()
    Output("Input_Halts = ", HO((u32)Infinite_Loop));
  Infinite_Loop()
[00001102](01) 55
[00001103](02) 8bec
[00001105](02) ebfe
[00001107](01) 5d
[00001108](01) c3
                                                           push ebp
                                                           mov ebp,esp
jmp 00001105
                                   8bec
                                   ebfe
                                                           pop ebp
                                                            ret
Size in bytes: (0007) [00001108]
_main()
[00001192](01)
[00001193](02)
[00001195](05)
[00001196](03)
[00001196](01)
[000011a2](01)
[000011a3](05)
[000011ad](03)
[000011b0](02)
[000011b2](01)
[000011b3](01)
Size in bytes:
                                                           push ebp
                                  8bec mov ebp, esp
6802110000 push 00001102
e8d3fbffff call 00000d72
83c404
                                   83c404
                                                           add esp,+04
                                  50 push eax
68a3040000 push 000004a3
e845f3ffff call 000004f2
                                   83c408
                                                           add esp,+08
                                                           xor eax, eax
                                   33c0
                                   5d
                                                           pop ebp
 Size in bytes:(0034) [000011b3]
  machine
                        stack
                                              stack
                                                                    machine
                                                                                             assembly
  address
                        address
                                                                    code
                                                                                             language
 [00001192][00101ef8][00000000] 55 push ebp
[00001193][00101ef8][00000000] 8bec mov ebp,esp
[00001195][00101ef4][00001102] 6802110000 push 00001102
[0000119a][00101ef0][0000119f] e8d3fbffff call 00000d72
HO: Begin Simulation Execution Trace Stored at:211fac [00001102][00211f9c][00211fa0] 55 push ebp [00001103][00211f9c][00211fa0] 8bec mov ebp,esp [00001105][00211f9c][00211fa0] ebfe jmp 00001105 [00001105][00211f9c][00211fa0] ebfe jmp 00001105 HO: Infinite Loop Detected Simulation Stopped
  return 1;
[0000119f][00101ef8][00000000] 83c404 add esp,+04 [000011a2][00101ef4][00000000] 50 push eax [000011a3][00101ef0][000004a3] 68a3040000 push 000004a3 [000011a8][00101ef0][000004a3] e845f3ffff call 000004f2
Input_Halts = 0
[000011ad][00101ef8][00000000] 83c408
[000011b0][00101ef8][00000000] 33c0
[000011b2][00101efc][00100000] 5d
[000011b3][00101f00][00000004] c3
                                                                                            add esp,+08
                                                                                            xor eax, eax
                                                                                            pop ebp
                                                                                             ret
Number of Instructions Executed(554) == 8 Pages
```

Example 02: H correctly determines that Infinite_Recursion() never halts

```
void Infinite_Recursion(int N)
     Infinite_Recursion(N);
  int main()
     Output("Input_Halts = ", H((u32)Infinite_Recursion, 0x777));
 push ebp
                                                     mov ebp,esp
                                8b4508
                                                     mov eax, [ebp+08]
                                                     push eax
call 000010f2
                                e8f4ffffff
                                83c404
                                                     add esp,+04
                                                     pop ebp
  Size in bytes:(0017) [00001102]
_main()
[000011b2](01)
[000011b3](02)
[000011b5](05)
[000011b4](05)
[000011b4](05)
[000011c4](03)
                                                     push ebp
                                8bec mov ebp,esp
6877070000 push 00000777
                                68f2100000 push 000010f2
e8aefdffff call 00000f72
                                83c408
                                                     add esp,+08
 [000011c4] (03)
[000011c7] (01)
[000011c8] (05)
[000011cd] (05)
[000011d2] (03)
[000011d5] (02)
[000011d7] (01)
[000011d8] (01)
                                                     push eax
                                68a3040000 push 000004a3
e820f3ffff call 000004f2
                                83c408
                                                     add esp,+08
                                                     xor eax,eax
                                33c0
                                5d
  Size in bytes:(0039) [000011d8]
   machine
                                          stack
                                                             machine
                                                                                   assembly
                      stack
   address
                      address
                                          data
                                                             code
                                                                                   language
  [000011b2] [00101f39] [0000000]
[000011b3] [00101f39] [00000000]
[000011b5] [00101f35] [0000777]
[000011ba] [00101f31] [000010f2]
[000011bf] [00101f2d] [000011c4]
                                                                                   push ebp
                                                            8bec mov ebp, esp
6877070000 push 000010f2
68f2100000 push 000010f2
                                                             e8aefdffff call 00000f72
H: Begin Simulation Execution Trace Stored at:111fe5 [000010f2] [00111fd1] [00111fd5] 55 push ebp [000010f3] [00111fd1] [00111fd5] 8bec mov ebp,esp [000010f5] [00111fd1] [00111fd5] 8b4508 mov eax,[ebp-1000010f8] [00111fc9] [000010fe] e8f4ffffff call 000010f2 [001011fc5] [00111fd1] 55 push ebp [000010f3] [00111fc5] [00111fd1] 8bec mov ebp,esp [000010f5] [00111fc5] [00111fd1] 8bec mov ebp,esp [000010f5] [00111fc1] [0000077] 50 push eax [000010f8] [00111fc1] [000010fe] e8f4ffffff call 000010f2 H: Infinite Recursion Detected Simulation Stopped
                                                                                  mov ebp,esp
mov eax,[ebp+08]
                                                             50 push eax // push 0x777
e8f4ffffff call 000010f2 // call Infinite_Recursion
                                                                                  mov eax, [ebp+08]
                                                            50 push eax // push 0x777
e8f4ffffff call 000010f2 // call Infinite_Recursion
 H: Infinite Recursion Detected Simulation Stopped
 (1) Infinite Recursion() is called twice in sequence from the same machine address of Infinite Recursion().
 (2) With the same parameters to Infinite Recursion()
 (3) With no control flow instructions between the invocation of Infinite Recursion() and the call to
 Infinite Recursion() from Infinite Recursion()
  [000011c4][00101f39][00000000] 83c408
[000011c7][00101f35][00000000] 50
[000011c8][00101f31][000004a3] 68a3040
[000011cd][00101f31][000004a3] e820f3
                                                                                   add esp,+08
                                                             50 push eax
68a3040000 push 000004a3
                                                             e820f3ffff call 000004f2
  Input_Halts = 0

[000011d2][00101f39][00000000]

[000011d5][00101f39][00000000]

[000011d7][00101f3d][00000018]

[000011d8][00101f41][0000000]
                                                             83c408
                                                                                   add esp,+08
                                                             33c0
                                                                                  xor eax, eax
                                                                                  pop ebp
                                                            5d
  Number of Instructions Executed(1118) == 17 Pages
```

Example 03: H(P,P) correctly determines that its input never halts

```
void P(ptr x)
    int Halt_Status = H(x, x);
if (Halt_Status)
                                                                                        From a purely software engineering
                                                                                        perspective (anchored in the semantics of
        HERE: goto HERE;
                                                                                        the x86 language) it is proven that H(P,P)
    return:
                                                                                        correctly predicts that its correct and
                                                                                        complete x86 emulation of its input would
 int main()
                                                                                        never reach the "ret" instruction (final state)
    Output("Input_Halts = ", H(P, P));
                                                                                        of this input. Copyright 2022 PL Olcott
[000013c6](01)
[000013c7](02)
[000013c9](01)
[000013ca](03)
[000013cd](01)
                                                                                               Save Base Pointer register onto the stack
Load Base Pointer with Stack Pointer
Save the value of ecx on the stack
                                                 push ebp
                             8bec
                                                 mov ebp, esp
                                                 push ecx
                             8b4508
                                                 mov eax, [ebp+08]
                                                                                               Load eax with argument to P
                                                                                               push 2nd argument to H onto the stack
                                                 push eax
                             50
                                                                                              push 2nd argument to H onto the stack
Load ecx with with argument to P
push 1st argument to H onto the stack
push return address on the stack; call simulated H
remove call arguments from stack
load Halt_Status with return value from H
compare Halt_Status to 0
  000013ce1(03)
                             8b4d08
                                                 mov ecx, [ebp+08]
                                                 push ecx
call 00001106
  000013d1
 [000013d1](01)
[000013d2](05)
[000013d7](03)
[000013da](03)
[000013dd](04)
                             e82ffdffff
                                                add esp,+08

mov [ebp-04],eax

cmp dword [ebp-04],+00 /

jz 000013e5
                             83c408
                             8945fc
                             837dfc00
 [000013d1](02)
[000013e3](02)
[000013e3](02)
[000013e7](01)
[000013e8](01)
                                                                                               if Halt_Status == 0 goto 000013e5
                             7402
                                                                                            / goto 13e3
/ Load Stack Pointer with Base Pointer
/ Restore Base_Pointer value from stack
                                                 jmp 000013e3
                             ebfe
                                                 mov esp,ebp
                             8be5
                             5d
                                                 pop ebp
                                                                                               return to caller
                                                  ret
 Size in bytes: (0035) [000013e8]
_main()
[000013f6](01)
[000013f7](02)
[000013f9](05)
[00001403](05)
[00001408](03)
[0000140b](01)
[0000140b](05)
[00001411](05)
[00001416](03)
[0000141b](01)
[0000141b](01)
[0000141b](01)
                                                                               Save Base Pointer register onto the stack
Load Base Pointer with Stack Pointer
                                                 push ebp
                             8bec mov ebp,esp /
68c6130000 push 000013c6 /
68c6130000 push 000013c6 /
e8fefcffff call 00001106 /
                                                                               Push P (2nd argument to H) onto the stack
Push P (1nd argument to H) onto the stack
                             e8fefcffff
                                                                               push return address onto the stack and call executed H
                                                                               remove call arguments from stack frame
                             83c408
                                                 add esp,+08
                             50 push eax //
6837050000 push 00000537 //
e870f1fffff call 00000586 //
                                                                               Push return value from H onto the stack
Push address of "Input_Halts = " onto the stack
call Output with its pushed arguments.
                             83c408
                                                 add esp,+08
                                                                               remove call arguments from stack frame
                             33c0
                                                 xor eax, eax
                                                                               set eax to 0
                             5d
                                                                               Restore Base Pointer register from stack
                                                 pop ebp
 [0000141c] (01)
                                                                               return to 0 operating system
 Size in bytes:(0039) [0000141c]
  machine
                    stack
                                      stack
                                                        machine
                                                                            assembly
  address
                    address
                                      data
                                                        code
                                                                            language
 [000013f6] [0010235f] [00000000] 55 push ebp
[000013f7] [0010235f] [00000000] 8bec mov ebp,esp
[000013f9] [0010235b] [000013c6] 68c6130000 push 000013c6 // Push P (2nd argument to H) onto the stack
[000013fe] [00102357] [000013c6] 68c6130000 push 000013c6 // Push P (1nd argument to H) onto the stack
[00001403] [00102353] [00001408] e8fefcffff call 00001106 // push return address; call executed H
H: Infinitely Recursive Simulation Detected Simulation Stopped
(1) Function H() is called from P().
(2) With the same arguments to H().
(3) With no control flow instructions in P preceding its invocation of H(P,P) that could escape repeated simulations.
 [00001408] [0010235f] [00000000] 83c408
[0000140b] [0010235b] [00000000] 50
[0000140c] [00102357] [00000537] 683705
[00001411] [00102357] [00000537] e870f1
                                                                            add esp.+08
                                                       50 push eax // Push return value from H onto the stack
6837050000 push 00000537 // Push address of "Input_Halts = " onto stack
e870f1ffff call 00000586 // call Output with its pushed arguments
[00001411] [00102357] [0000000]

Input_Halts = 0

[00001416] [0010235f] [00000000]

[00001419] [0010236f] [00000000]

[00001416] [00102367] [000000000]

[00001416] [00102367] [000000000]
                                                       83c408
                                                                            add esp,+08
                                                       33c0
                                                                           xor eax, eax
                                                                                                     // set eax to 0
                                                       5d
                                                                            pop ebp
                                                       с3
                                                                                                     // return to 0 operating system
                                                                            ret
 Number of Instructions Executed (987) == 15 Pages
```

Halt Decider source-code

```
#include <stdio.h>
#include <stdint.h>
 #include <stdlib.h>
#include <time.h>
#pragma warning (disable: 4717)
//#define OUTPUT_SIMULATED_LINE
#define u8 uint8_t
#define u32 uint32_t
#define u16 uint16_t
#define s8 int8_t
#define s16 int16_t
#define s32 int32_t
typedef void (*ptr)();
 typedef struct x86_Registers
        u32 EIP:
        u32 EAX;
        u32
                        EBX;
        u32
                         ECX;
        u32
                          EDX;
        u32
                           ESI;
        u32
                           EDI;
        u32
                          EBP;
        u32
                          ESP;
        u32
                         EFLG;
        u16 CS;
        u16 SS;
        u16 DS;
        u16 ES;
        u16 FS;
u16 GS;
} Registers;
#define
#
typedef struct Decoded
{
        u32 Address;
        u32 ESP;
                                                                            // Current value of ESP
        u32 TOS; // C
u32 NumBytes;
u32 Simplified_Opcode;
                                                                            // Current value of Top of Stack
        u32 Decode_Target;
} Decoded_Line_Of_Code;
u8 BEGIN[] = "BEGIN STATIC DATA"; // Required to force allocation
u32 Heap_PTR = 0x11111111; // forces memory allocation u32 Heap_END = 0x22222222; // forces memory allocation
u32 Heap_END = 0x22222222; // for u8 END[] = "END STATIC DATA";
                                                                                                                                           // Required to force allocation
```

```
// Empty Stub Functions of Virtual Machine Instructions
// x86utm operating system calls
void OutputString(char* S) {}
void Output(char* S, u32 N) {}
u32* Allocato(u22 size) { ret
u32 Infinite_Loop_Needs_To_Be_Aborted_Trace
    (Decoded_Line_Of_Code* execution_trace, Decoded_Line_Of_Code *current)
  Decoded_Line_Of_Code *traced;
  u32 Conditional_Branch_Count = 0;
                                    // 2021-04-06
// 2021-04-06
  u32* ptr = (u32*)execution_trace;
  u32 size = ptr[-1]; // 2021-04-06
u32 next2last = (size/sizeof(Decoded_Line_Of_Code)) -2;
  for (s32 N = next2last; N >= 0; N--)
    traced = &execution_trace[N];
                                                           // JCC
    if (traced->Simplified_Opcode == JCC)
      Conditional_Branch_Count++;
    if (current->Simplified_Opcode == JMP)
                                                           // JMP
                                                           // upward
      if (current->Decode_Target <= current->Address)
        if (traced->Address == current->Decode_Target)
                                                           // to this address
          if (Conditional_Branch_Count == 0)
                                                           // no escape
            return 1:
  return 0;
u32 Infinite_Recursion_Needs_To_Be_Aborted_Trace
    (Decoded_Line_Of_Code* execution_trace, Decoded_Line_Of_Code *current)
  Decoded_Line_Of_Code *traced;
  u32 Conditional_Branch_Count = 0;
                                     // 2021-04-06
// 2021-04-06
  u32* ptr = (u32*)execution_trace;
  u32 size = ptr[-1]; // 2021-04-06
u32 next2last = (size/sizeof(Decoded_Line_Of_Code)) -2;
  for (s32 N = next2last; N >= 0; N--)
    traced = &execution_trace[N];
    if (traced->Simplified_Opcode == JCC)
                                                           // JCC
      Conditional_Branch_Count++;
    if (current->Simplified_Opcode == CALL)
      if (current->Simplified_Opcode == traced->Simplified_Opcode) // CALL
        if (current->Address == traced->Address)
          if (Conditional_Branch_Count == 0)
                                                             // no escape
              return 2;
  return 0;
```

```
u32 Infinite_Simulation_Needs_To_Be_Aborted_Trace
    (Decoded_Line_Of_Code* execution_trace,
     Decoded_Line_Of_Code *current, u32 P, u32 I)
  Decoded_Line_Of_Code *traced;
  u32 Count_PUSH_Instructions = 0;
  u32 Num_PUSH_Matched
                                = 0;
  u32 Conditional_Branch_Count = 0;
                                       // 2021-04-06
// 2021-04-06
  u32* ptr = (u32*)execution_trace;
  u32 \text{ size} = ptr[-1];
  u32 next2last = (size/sizeof(Decoded_Line_Of_Code)) -2;
  for (s32 N = next2last; N \geq 0; N--)
    traced = &execution_trace[N];
    if (traced->Simplified_Opcode == JCC)
                                                             // JCC
      Conditional_Branch_Count++;
    if (traced->Simplified_Opcode == PUSH)
                                                             // PUSH
      Count_PUSH_Instructions++;
    if (traced->Simplified_Opcode == PUSH &&
        traced->Decode_Target == P && Count_PUSH_Instructions == 1)
      Num_PUSH_Matched++;
    if (traced->Simplified_Opcode == PUSH &&
        traced->Decode_Target == I && Count_PUSH_Instructions == 2)
      Num_PUSH_Matched++:
    if (Num_PUSH_Matched == 2 && N == 0 && Conditional_Branch_Count == 0)
      return 3:
  return 0;
u32 Needs_To_Be_Aborted(Decoded_Line_Of_Code* execution_trace,
                         u32 Address_of_H, u32 P, u32 I)
u32 Aborted = 0;

u32* ptr = (u32*)execution_trace; // 2021-04-06

u32 size = ptr[-1]; // 2021-04-06

//output("Needs_to_Be_Aborted(size):", size);
  Decoded_Line_Of_Code* current = &execution_trace[last];
  if (current->Simplified_Opcode == CALL)
    if (current->Decode_Target == Address_of_H)
      Aborted = Infinite_Simulation_Needs_To_Be_Aborted_Trace
                 (execution_trace, current, P, I);
      Aborted = Infinite_Recursion_Needs_To_Be_Aborted_Trace
                 (execution_trace, current);
  else if (current->Simplified_Opcode == JMP)
    Aborted = Infinite_Loop_Needs_To_Be_Aborted_Trace(execution_trace, current);
  return Aborted;
}
```

```
This is called every time the a line ocf x86 code is emulated
u32 Decide_Halting(char*
                                                          Halt_Decider_Name,
                                                          execution_trace,
                         u32*
                         Decoded_Line_Of_Code**
                                                          decoded.
                         u32
                                                          code_end,
                         Registers**
                                                          master_state,
                         Registers**
u32**
                                                          slave_state,
                                                          slave_stack,
                         u32
                                                          Address_of_H, u32 P, u32 I)
  u32 Aborted = 0;
  while (Aborted == 0)
     #ifdef OUTPUT_SIMULATED_LINE
     Output_Decoded((u32)*decoded);
#endif
    When we are not recursively simulatng H we don't need this is statement if (EIP > Last_Address_Of_Operating_System()) // Don't examine any OS code PushBack(*execution_trace, (u32)*decoded, sizeof(Decoded_Line_Of_Code)); Aborted = Needs_To_Be_Aborted((Decoded_Line_Of_Code*)*execution_trace, Address_of_H, P, I);
  if (Aborted) // 2021-01-26 Must be aborted
     OutputString(Halt_Decider_Name);
     if (Aborted == 1)
  OutputString("Infinite Loop Detected Simulation Stopped\n\n");
if (Aborted == 2)
  OutputString("Infinite Recursion Detected Simulation Stopped\n\n");
if (Aborted == 3)
       OutputString("Infinitely Recursive Simulation Detected "
"Simulation Stopped\n\n");
     return 0;
                          // 2021-01-26 Need not be aborted
  return 1;
// This only works with ONE PARAMETER to the called function
void Init_slave_state(u32 P, u32 I, u32 End_Of_Code,
                             Registers* slave_state, u32* slave_stack)
  u32 Top_of_Stack;
  u32 Capacity;
  u32 Size;
  Top_of_Stack = StackPush(slave_stack, I);  // Data for Function to invoke
Top_of_Stack = StackPush(slave_stack, End_Of_Code); // Return Address in Halts()
  SaveState(slave_state);
                                     // Based on this point in execution
  Capacity = slave_stack[-2];
  Size = slave_stack[-1];
  slave_state->EIP = P;  // Function to invoke
slave_state->ESP = Top_of_Stack;
  slave_state->EBP = Top_of_Stack;
```

```
u32 H(ptr P, ptr I)
HERE:
  u32 End_Of_Code;
                                          // 2022-06-17
  u32 Address_of_H;
  u32 code_end = get_code_end((u32)P);
Decoded_Line_Of_Code *decoded = (Decoded_Line_Of_Code*)
Allocate(sizeof(Decoded_Line_Of_Code));
                                        = (Registers*) Allocate(sizeof(Registers));
= (Registers*) Allocate(sizeof(Registers));
  Registers* master_state
                 slave_state
  Registers*
  u32* slave_stack = Allocate(0x10000); // 64k;
u32 execution_trace = (u32)Allocate(sizeof(Decoded_Line_Of_Code) * 10000);
                                           // 10000 lines of x86 code
// 2022-06-18
// 2022-06-18
// 2022-06-18
  __asm lea eax, HERE
  __asm sub eax, 6
__asm mov Address_of_H, eax
    _asm mov eax, END_OF_CODE
_asm mov End_Of_Code, eax
  &slave_state, &slave_stack, Address_of_H, (u32)P, (u32)I))
goto END_OF_CODE;
return 0; // Does not halt
END_OF_CODE:
  OutputString("H: End Simulation
                                             Input Terminated Normally\n\n");
   return 1; // Input has normally terminated
// Dummy Place holder needed to know where
// the x86utm operating system is located.
// THIS FUNCTION MAY BE OBSOLETE
u32 Halts(u32 P, u32 I)
   return 0;
void P(ptr x)
   int Halt_Status = H(x, x);
if (Halt_Status)
     HERE: goto HERE;
   return;
int main()
  Output("Input_Halts = ", H(P, P));
```

Appendix (Simulating halt decider applied to Peter Linz proof)

The following is the same idea a shown above this time it is applied to the Peter Linz Halting Problem proof. It can only be undertood within the context of this proof.

A simulating halt decider (SHD) computes the mapping from its inputs to its own final states on the basis of the behavior of its correctly simulated input.

All of the conventional halting problem counter-example inputs are simply rejected by a simulating halt decider as non-halting because they fail to meet the Linz definition of halting:

computation that halts ... the Turing machine will halt whenever it enters a final state. (Linz:1990:234)

USENET comp.theory: On 4/11/2022 3:19 PM, Malcolm McLean wrote:

- > PO's idea is to have a simulator with an infinite cycle detector.
- > You would achieve this by modifying a UTM, so describing it as
- > a "modified UTM", or "acts like a UTM until it detects an infinite
- > cycle", is reasonable. And such a machine is a fairly powerful
- > halt decider. Even if the infinite cycle detector isn't very
- > sophisticated, it will still catch a large subset of non-halting
- > machines.

The following simplifies the syntax for the definition of the Linz Turing machine \hat{H} . There is no need for the infinite loop after H.qy because it is never reached. The halting criteria has been adapted so that it applies to a simulating halt decider (SHD).

 $\hat{H}.q_0 \langle \hat{H} \rangle \vdash^* H \langle \hat{H} \rangle \langle \hat{H} \rangle \vdash^* \hat{H}.qy$

If the correctly simulated input $\langle \hat{H} \rangle \langle \hat{H} \rangle$ to H would reach its own final state of $\langle \hat{H}.qy \rangle$ or $\langle \hat{H}.qn \rangle$.

 $\hat{H}.q_0 \langle \hat{H} \rangle \vdash^* H \langle \hat{H} \rangle \langle \hat{H} \rangle \vdash^* \hat{H}.qn$

If the correctly simulated input $\langle \hat{H} \rangle$ to H would never reach its own final state of $\langle \hat{H}, qy \rangle$ or $\langle \hat{H}, qn \rangle$.

When \hat{H} is applied to $\langle \hat{H} \rangle$ // subscripts indicate unique finite strings \hat{H} copies its input $\langle \hat{H}_0 \rangle$ to $\langle \hat{H}_1 \rangle$ then H simulates $\langle \hat{H}_0 \rangle \langle \hat{H}_1 \rangle$

Then these steps would keep repeating: (unless their simulation is aborted)

 \hat{H}_0 copies its input $\langle \hat{H}_1 \rangle$ to $\langle \hat{H}_2 \rangle$ then H_0 simulates $\langle \hat{H}_1 \rangle \langle \hat{H}_2 \rangle$

 \hat{H}_1 copies its input $\langle \hat{H}_2 \rangle$ to $\langle \hat{H}_3 \rangle$ then H_1 simulates $\langle \hat{H}_2 \rangle$ $\langle \hat{H}_3 \rangle$

 \hat{H}_2 copies its input $\langle \hat{H}_3 \rangle$ to $\langle \hat{H}_4 \rangle$ then H_2 simulates $\langle \hat{H}_3 \rangle$ $\langle \hat{H}_4 \rangle ...$

Since we can see that the simulated input: $\langle \hat{H}_0 \rangle$ to H would never reach its own final state of $\langle \hat{H}_0.qy \rangle$ or $\langle \hat{H}_0.qn \rangle$ we know that it is non-halting.

Linz, Peter 1990. An Introduction to Formal Languages and Automata. Lexington/Toronto: D. C. Heath and Company. (317-320) this paper copyright 2022 by PL Olcott

Infinite recursion / infinitely recursive emulation detection criteria

```
int H(ptr p, ptr i)
{
   p(i);
}

void P(ptr x)
{
   H(x, x);
   return;
}
int main()
{
   H(P,P);
}
```

If the execution trace of function P() called by function H() shows:

- (1) Function H() is called twice in sequence from the same machine address of P().
- (2) With the same parameters to H().
- (3) With no control flow instructions between the invocation of P() and the call to H() from P().

Then the function call from P() to H() is infinitely recursive.

The exact same pattern applies when H() invokes simulate(p,i) with an x86 emulator.

When H is an infinite recursion detector it simply matches the above criteria in its execution trace of P, aborts its simulation of its input and reports that its simulated input would never reach its "return" instruction.

To avoid using static local memory for its stored execution trace H must know its own address and see itself called from P with the same arguments that it was called with.

https://www.liarparadox.org/2022_07_22.zip
This is the complete system that compiles under:

Microsoft Visual Studio Community 2017

https://visualstudio.microsoft.com/vs/older-downloads/

It has not been recently compiled under UBUNTU

If a simulating halt decider continues to correctly simulate its input until it correctly matches a non-halting behavior pattern then this SHD is necessarily correct when it aborts its simulation and reports non-halting.

```
*Halt Decider and P*
07/22/2022 07:05 AM
07/22/2022 07:09 AM
                                      10,390 Halt7.c
                                       3,989 Halt7.obj
*x86utm operating system*
07/22/2022 07:08 AM
07/01/2022 03:40 PM
                                      72,499 x86utm.cpp
                                      32,931 Read_COFF_Object.h
*x86 emulator source-code*
10/04/2020 07:44 PM
05/03/2021 02:33 PM
06/28/2020 05:22 PM
06/30/2020 12:06 AM
06/27/2022 11:15 AM
06/30/2020 02:09 AM
                                      17,240 api.c
                   02:33 PM
05:22 PM
12:06 AM
                                      58,872 decode.c
                                    20,495 mem.c
141,330 ops.c
63,704 ops2.c
                                      73,787 prim_ops.c
01/28/2020
                   06:19 AM
                                       5,542 decode.h
                   08:56 PM
02/17/2020
                                      18,558 getopt.h
01/28/2020 06:19 AM
01/28/2020 06:19 AM
                                       1,859 mem.h
                                       1,954 ops.h
01/28/2020 06:19 AM
02/09/2021 10:40 PM
10/04/2020 07:34 PM
                                     6,133 prim_ops.h
19,596 x86emu.h
4,996 x86emu_int.h
```

Compiles into x86utm.exe and takes Halt7.obj as its only argument

This is how we verify that the simulation is correct

In programming language theory, semantics is the field concerned with the rigorous mathematical study of the meaning of programming languages.[1] It does so by evaluating the meaning of syntactically valid strings defined by a specific programming language, showing the computation involved. In such a case that the evaluation would be of syntactically invalid strings, the result would be non-computation. Semantics describes the processes a computer follows when executing a program in that specific language.

https://en.wikipedia.org/wiki/Semantics_(computer_science)

We verify that the execution trace of the simulated input has the behavior that the simulated x86 source-code specifies, line-by-line.

For any program H that might determine if programs halt, a "pathological" program P, called with some input, can pass its own source and its input to H and then specifically do the opposite of what H predicts P will do. No H can exist that handles this case.

https://en.wikipedia.org/wiki/Halting_problem

That when any TM or C simulating halt decider H correctly simulates any input matching the above defined "pathological" input template P, that P presents the infinitely recursive non-halting behavior pattern to H.

Furthermore H can correctly use this pattern match as its basis to abort its simulation and correctly reject this input as non-halting.

WE STAY FOCUSED ON THIS POINT UNTIL FULLY UNDERSTOOD

It has been conclusively proven that the correctly simulated input to H(P,P) correctly simulated by H cannot possibly reach its "return" instruction.

```
[000013c6] (01)
[000013c7] (02)
                                     push ebp
                      8bec
                                     mov ebp,esp
 000013c9
                                     push ecx
                      51
 000013ca]
                      8b4508
                                     mov eax, [ebp+08]
 000013cd](01)
                                     push eax
                                     mov ecx, [ebp+08]
 000013ce]
                      8b4d08
                                     push ecx
call 00001106
 000013d1
                      e82ffdffff
 000013d2
                                     add esp,+08
mov [ebp-04],eax
 000013d7]
                      83c408
 000013da]
                      8945fc
                                     cmp dword [ebp-04],+00
jz 000013e5
jmp 000013e3
 000013dd](04)
                      837dfc00
[000013d1](02) 7402 jz 0
[000013e1](02) 7402 jz 0
[000013e3](02) ebfe jmp
[000013e5](02) 8be5 mov
[000013e7](01) 5d pop
[000013e8](01) c3 ret
Size in bytes:(0035) [000013e8]
                                     mov esp,ebp
We have to do this at the C level.
void P(ptr x)
    int Halt_Status = H(x, x);
   if (Halt_Status)
       HERE: goto HERE;
   return;
int main()
   Output("Input_Halts = ", H(P, P));
```

H(P,P) simulates its input then P calls H(P,P) to simulate itself and if H did simulate it then the simulated P would call H(P,P) again and if H did simulate it then the simulated P would call H(P,P) again and if H did simulate it then the simulated P would call H(P,P) again and if H did simulate it then the simulated P would call H(P,P) again and if H did simulate it then the simulated P would call H(P,P) again

Can you see the repeating pattern?

Example 05: P(P) halts because H(P,P) correctly determines that its input never halts

This conclusively proves that H(P,P) correctly simulates its input and that the behavior of the correctly simulated P is very different than the directly executed P(P).

The correctly simulated P cannot possibly terminate normally by reaching its own "return" instruction. The executed P does terminate normally and reaches its own "return" instruction.

If you are not an expert in the x86 language then you lack the basis to determine that the input to H(P,P) is not simulated correctly. The strongest claim that you can make is that on the basis that you do not understand the x86 language you do not understand the proof.

```
typedef void (*ptr)();
int H(ptr p, ptr i); // simulating halt decider
void P(ptr x)
    int Halt_Status = H(x, x);
   if (Halt_Status)
       HERE: goto HERE;
    return;
int main()
   P(P);
_P()
[0000143b] (01)
[0000143c] (02)
[0000143c] (01)
[0000143c] (03)
[00001442] (01)
[00001446] (01)
[00001447] (05)
[0000144c] (03)
[0000144c] (03)
[0000145c] (04)
[0000145a] (02)
[0000145c] (01)
Size in bytes:
                                                        push ebp
                             8bec
                                                        mov ebp,esp
                             51
                                                        push ecx
                             8b4508
                                                        mov eax, [ebp+08]
                                                        push eax
                             50
                             8b4d08
                                                        mov ecx, [ebp+08]
                                                        push ecx
call 000010fb
                             51
                             e8affcffff
                            83c408
8945fc
                                                       add esp,+08
mov [ebp-04],eax
cmp dword [ebp-04],+00
jz 0000145a
jmp 00001458
                             837dfc00
                             7402
                             ebfe
                             8be5
                                                        mov esp,ebp
                             5d
                                                        pop ebp
                                                        ret
Size in bytes:(0035) [0000145d]
_main()
[0000146b] (01)
[0000146c] (02)
[0000146e] (05)
[00001473] (05)
[00001478] (03)
[00001476] (02)
                                                        push ebp
                                                        mov ebp,esp
push 0000143b
                             8bec
                             683b140000
                             e8c3ffffff
                                                        call 0000143b
                             83c404
                                                        add esp,+04
                                                        xor eax, eax
                             33c0
 0000147d]
                             5d
                                                        pop ebp
[0000147e] (01)
                                                        ret
Size in bytes:(0020) [0000147e]
 machine
                    stack
                                      stack
                                                        machine
                                                                            assembly
 address
                    address
                                      data
                                                        code
                                                                            language
                                     [00000000]
 [0000146b]
                  [00102428]
                                                                            push ebp
                                                                           mov ebp,esp
push 0000143b
call 0000143b
 "0000146c
                   [00102428<sup>-</sup>
                                     [00000000]
                                                        8bec
 0000146e
                   00102424
                                     [0000143b]
                                                        683b140000
                                                                                                               push P
                   00102420
                                     00001478
 00001473
                                                        e8c3ffffff
                                                                                                                call P with argument on stack
 [0000143b]
                   0010241c
                                     00102428
                                                                            push ebp
                                                                                                                enter executed P
 0000143c
                   0010241c
                                     00102428
                                                        8bec
                                                                            mov ebp,esp
[0000143c] [0010241c] [00102428] [0000143c] [00102418] [00000000] [0000143f] [00102418] [00000000] [00001442] [00102414] [0000143b] [00001446] [00102414] [0000143b] [00001446] [00102410] [0000143b] [00001447] [0010240c] [0000144c]
                                                                            push ecx
                                                       8b4508 mov eax,[ebp+08] // load eax with argument to P
50 push eax // push P from eax
8b4d08 mov ecx,[ebp+08] // load ecx with argument to P
51 push ecx // push P from ecx
e8affcffff call 000010fb // call executed H with argument
                                                        51
                                                                                                           // call executed H with arguments on stack
```

When simulating halt decider H(P,P) simulates its input it can see that:

- (1) Function H() is called from P().
- (2) With the same arguments to H().
- (3) With no instructions in P preceding its invocation of H(P,P) that could escape repeated simulations.

The above shows that the simulated P cannot possibly (reachs its "return" instruction and) terminate normally. H(P,P) simulates its input then P calls H(P,P) to simulate itself again. When H sees that this otherwise infinitely nested simulation would never end it aborts its simulation of P and rejects P as non-halting.

```
add esp,+08
mov [ebp-04],eax
cmp dword [ebp-04],+00 //
jz 0000145a
mov esp,ebp
                                                                                                                                                                                    // return to executed P
// load Halt_Status with return value
// if Halt_Status == 0
// goto 0000145a
[0000144c] [00102418] [00000000] [0000144f] [00102418] [00000000] [00001452] [00102418] [00000000] [00001456] [00102418] [00000000]
                                                                                     83c408
                                                                                     8945fc
837dfc00
[00001452] [00102418] [00000000] [00001452] [00102418] [00000000] [0000145a] [0010241c] [00102428] [00001478] [00102424] [00001478] [00102424] [00001478] [00102424] [00001478] [00102428] [00000000] [0000147b] [00102428] [00000000] [0000147d] [0010242c] [000000018] [0000147d] [0010242c] [000000000] [0000147d] [00102430] [000000000] [0000147d] [00102430] [000000000]
                                                                                      7402
                                                                                      8be5
                                                                                      5d
                                                                                                                    pop ebp
                                                                                                                                                                                     // return from executed P to main
                                                                                                                     ret
                                                                                                                     add esp,+04
                                                                                      83c404
                                                                                     33c0
                                                                                                                    xor eax, eax
                                                                                                                                                                                     // set eax to 0
                                                                                                                     pop ebp
                                                                                                                                                                                     // return from main to operating system
[0000147e][00102430][00000000] c3 ret
Number of Instructions Executed(998) == 15 Pages
```